

INSTALLATION INSTRUCTIONS



WARLOCK MUFFLERS FOR 86-93 MUSTANG 5.0L



PART#	DESCRIPTION
50551B	2 1/4" IN/OUT OFFSET/OFFSET
50552B	2 1/2" IN/OUT OFFSET/OFFSET
50560B	3" IN/OUT OFFSET/OFFSET

WARLOCK™ MUFFLERS ARE DESIGNED, FABRICATED AND BUILT WITH PRIDE OF WORKMANSHIP BY HANDS-ON CAR ENTHUSIASTS AT OUR MODERN FACILITY LOCATED IN TEMPE, ARIZONA. .


READ THESE INSTRUCTIONS CAREFULLY BEFORE STARTING: FOR EASE OF INSTALLATION, YOUR VEHICLE MUST BE RAISED A MINIMUM OF 36". WARNING SHOULD YOU DECIDE TO INSTALL ANY EXHAUST YOURSELF, BE WARNED THAT THE ORIGINAL EQUIPMENT JACK THAT CAME WITH THE VEHICLE IS INTENDED FOR EMERGENCY USE ONLY. THE USE OF A FRAME JACK IN CONJUNCTION WITH A FLOOR JACK AS MAIN SUPPORT IS HIGHLY RECOMMENDED TO MINIMIZE THE ACCIDENTAL DROPPING OF A VEHICLE WHILE THE INSTALLATION PROCEEDS. NEVER GO UNDER ANY VEHICLE THAT IS SUPPORTED BY A BUMPER JACK!

WHEN INSTALLING THE WARLOCK™ BYPASS OR THE WARLOCK™ STANDARD SERIES RACING MUFFLERS ON ANY 1986-1993 MUSTANG YOU MUST SHORTEN THE FRONT INTERMEDIATE PIPES 4 3/4" TO 5" AND INSTALL THE MUFFLERS FORWARD TO LINE UP THE ROD HANGERS AND ALLOW FOR ACCESS TO REMOVE THE "FLOW INTENSIFIER".

THERE SHOULD BE 5" BETWEEN THE REAR-END BALANCING WEIGHT AND THE BACK EDGE OF THE MUFFLER CASE.

NOTE: BECAUSE YOU HAVE MOVED THE MUFFLERS FORWARD, IT MAY BE NECESSARY TO ADD TUBING OR TO MODIFY THE FRONT SECTION OF YOUR TAILPIPES TO INSTALL THEM IN THE MUFFLER OUTLETS.

SEE ILLUSTRATIONS "A", "B", AND "C" FOR DETAILS.



INSTALL 1/2" PUSH NUTS OVER ROD HANGER

PASSENGER SIDE: CUT OFF EXCESS THREAD ON THE ROD-HANGER

ILLUSTRATION "A"




ILLUSTRATION "B"

PROPER ROD-HANGER  
INSTALLATION

LEAVE 5" INCHES OF CLEARANCE BETWEEN REAR-  
END AND TO THE BACK EDGE OF THE MUFFLER CASE

HOW DID WE DO? YOUR QUESTIONS AND INPUT ARE ALWAYS WELCOME AT FLOWTECH® OUR TECHNICAL SERVICES DEPARTMENT IS OPEN MONDAY THROUGH FRIDAY, DURING THE HOURS OF 8:30AM UNTIL 4:30PM MOUNTAIN TIME. WE CAN BE REACHED AT:

**FLOWTECH®**  
by **Holley®**

THE PERFORMANCE EXHAUST COMPANY™

1801 Russellville Road • Bowling Green, KY 42102  
PHONE 270-781-9741 • FAX 270-781-9772



ILLUSTRATION "C"

LIT PN50551B REVISED 03/16/00

**LIMITATION OF LIABILITY - DISCLAIMER:** THE REGULATION OF EMISSIONS PRODUCTION, NOISE LEVELS AND SAFETY STANDARDS IS UNDERTAKEN BY THE FEDERAL GOVERNMENT, EACH OF THE FIFTY STATE LEGISLATURES AND BY MANY LOCAL MUNICIPALITIES, TOWNS AND COUNTRIES.

FLOWTECH® MAKES NO WARRANTIES OF MERCHANTABILITY, OF FITNESS FOR PARTICULAR PURPOSE. OR THAT ITS PRODUCTS ARE APPROVED FOR GENERAL USE, OR THAT ITS PRODUCTS COMPLY WITH LAWS, REGULATIONS OR ORDINANCES IN THE STATES WHERE THEY MAY BE SOLD TO THE ULTIMATE PURCHASER, THE CONSUMER.

UNLESS EXPRESSLY STATED TO THE CONTRARY IN THE ACCOMPANYING CATALOG, INSTRUCTION SHEET OR PRICE LIST, THE ENTIRE RISK AS TO THE CONFORMITY OF ANY COMPANY PRODUCT IN ANY SUCH STATE AND AS TO REPAIR SHOULD THE PRODUCT PROVE TO BE DEFECTIVE OR NONCONFORMING, IS ON THE RETAIL PURCHASER, THE BUYER, THE ULTIMATE CONSUMER, OF SUCH PRODUCT AND IT IS NOT UPON THE SELLER, DISTRIBUTOR OR MANUFACTURER.

IN THE CONNECTION, RETAIL PURCHASER, THE BUYER, THE ULTIMATE CONSUMER ASSUMES THE BURDEN OF THE ENTIRE COST OF ANY AND ALL NECESSARY SERVICE, ALTERATIONS OR REPAIR.